Figure 1



Figure 2a


218
LOAD
216
200
220
Power Management Circuitry
211
Power Management Application
201
Power Management Component #1
202
Power Management Component #2
203
Power Management Component #N
212
Protocol Stack Layer
213
Data Communications Interface
215

Figure 2b


280
281
240
283
LOAD
IED
281
240
282
Power Management Circuitry
290
250
Data Collection Component
251
Device Management Component
252
Billing/Revenue Management Component
253
Automated Meter Reading Component
254
Distributed Power Management Component
255
Centralized Power Management Component
256
Power Reliability Component
257
Peer to Peer Power Management Component
258
Usage/ Consumption Management Component
259
Load Management Component
260
Electrical Power Generation Management Component
261
IED Inventory Component
262
IED Maintenance Component
263
IED Fraud Detection Component
264
Power Quality Monitoring Component
265
Power Outage Component
284
Protocol Stack
286
Data Communications Interface
283

Figure 3a


302
A
B
C
IED
305
305a
CPU
Data Measurement
305b
or Power Management
Control Functions
300
305c
Memory
305d
Software Applications
305e
Protocol Stack Architecture
301
LOAD
306
Data Communications
Interface
307

Figure 3b


317
LOAD
316
310
320
Power Management Circuitry
311
Power Management Application
315a
Load Management Component
315b
Power Quality Component
315c
Billing/Revenue Management Component
312
Protocol Stack
313
Data Communications Interface
Network
Customer or Utility
Back End Server
Billing/Revenue Management Component

Figure 3c


IED 310
305e
Protocol Stack
Application Layer 321
Transport Layer 322
Routing Layer 323
Switching Layer 324
Interface Layer 325
Raw Data 330
Security Sub-layer 321a
Email Protocol Packaging 321b
326
IP

Figure 4a


A
B
C
402
IED
400
410
401
LOAD
411
Power
Management
Application
Components

Figure 4b


kWh or kVa pulse sent to IED
420
IED translates pulse to data
422
Data transported over network to power managament application components
424
Data requiers pre-processing .
425a
425b
(optional) Bypass data collection
Back end server processes message and transports data appropriate component. Data is processed into readable format for billing/revenue management component
426
Data sent to billing/revenue management component
428
billing/revenue management component computes revenue billing, usage and consumption and compares data against tariff structure
430
Has received data met tariff structure?
432
no
yes
Send power management function command to IED via back end server to control load and power flow distribution accordingly
434
Contact Consumer and Distributor of power distribution system with revenue billing, usage or consumption data
436

Figure 5a

Figure 5b



Figure 6


600
Electrical Power Distribution System
IED
616
IED
618
601
620
IED
LOAD
621
610
622
IED
LOAD
623
624
IED
Generator
625
626
IED
Generator
627

Figure 7



Figure 8


812
814
Customer Billing Server
800
IED
803
804
806
IED
LOAD
810
Power Utility
802
808
IED
LOAD
801

Figure 9


908
Power Utility
906
903
Power Generator
Utility Billing Server
900
902
910
IED
905
920
Customer
921
LOAD
901
922
Alert Pager
Customer Monitoring Server

Figure 10


1000
1002
IED
1001
LOAD
1010
1011
Excel
1020
Visio
1021
Exchange Server
1022
Excel Workbooks
1023

Site1.a8500

Default Diagram

LABEL	VALUE
I a	197.97
I b	207.52
I c	237.82
Vln c	479.28
Vln b	371.46
Vll ca	580.46
Vll ab	589.1
Vll bc	586.28
Vll avg	585.28
Vln avg	357.23
I avg	214.44
PF sign tot	-94
Freq	59
CL1 LocalTime	08:32.9
Sum of Currents:	643.31
Formula-based Setpoint:	OVER 550 Volts

Change Update Rate 10
Type in the number of seconds you would like between page updates and hit <RETURN>

Some features to implement:
Auto-detection: Excel could automatically add a worksheet (a "tab" below) when it detects a new device on the network
Complex Aggregation: Because it is Excel, you can do anything you want, easily
Logging: You could write simple scripts to log the values on the left to an Access DE
Animation: Charts, warnings, etc
Onboard logs could be displayed easily
Default diagrams: we just need to create an excel template for each device



Figure 11



Figure 12



Figure 13


1405
Customer C
1412
IED
1420
1410
Network
Firewall
1416
Mail Server
1450
Internet
1460
1452
Mail Server
1454
Database

Figure 14